

OPTICON

Windows Mobile

 Windows Mobile **GSM/GPRS/EDGE**

Single cradle
Multi-cradle

 **WiFi™**

 **Bluetooth™**

GPS

MiniSD I/O

H19B

2D CMOS imager



+ Related products

H19A

- Windows Mobile
- Barcode laser scanner
- Bluetooth, W-LAN (WiFi), GSM/GPRS/EDGE, miniSD I/O
- GPS



PHL7254

- Windows CE
- 2D CMOS imager
- Bluetooth, W-LAN (WiFi), GSM/GPRS, serial connector
- IP 54, Full keypad



PX25

- Data Collector
- 2D CMOS imager
- IrDA, Bluetooth
- Equipped with powerjack



Operation

- CPU: Samsung S3C2440A 400 Mhz
- O/S: Microsoft® Windows Mobile® 6 Professional
- Software: Excel Mobile, Powerpoint Mobile, Word Mobile, Internet Explorer, ActiveSync, Internet sharing, Pocket MSN, Phone application, Opticon scanner application, Accessories
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

Memory

- FlashROM: 512 MB
- RAM: 64 MB
- Expansion: User accessible mini SD

Display

- Type: Graphic Transflective TFT LCD with touch panel, 16-bit color with adjustable backlight
- Size: 2.8", 240 x 320 pixels
- Mode: Portrait / Landscape

Operating indicators

- Visual: 2 LEDs (red/orange/green/ blue)
- Non-visual: Vibrate, Speaker (.wav)

Operating keys

- Entry options: 24 keys total, 12 key (alpha)numeric keypad, 5-way navigation keys, function key, backspace key, 1 power key, 2 quick/hot keys, 2 phone keys, reset key, volume key, voice record, 2 scan keys, virtual keyboard, handwriting recognition

Communication

- USB: Mini USB, Ver. 1.1, client
- Bluetooth: Ver. 1.2, range up to 10 m
- W-LAN: WiFi, IEEE.802.11b/g
- "Telecom: GSM/GPRS/EDGE, quad-band 850/900/1800/1900, GSM Class 12, EDGE Class 10"
- GPS: NMEA 0183, SiRF Star III, 57.6 kbps
- Audio: Speaker/microphone (mono), headset connector (stereo)
- Extension: User accessible miniSD I/O

Power

- Rechargeable battery: Lithium-Ion Polymer, 4.2 V 1440 mAh
- High-capacity battery: Optional 4.2 V 2600 mAh
- Backup battery: Lithium rechargeable
- Operating time: Talk time 4 hours, Standby time 150 hours
- Data retention time: Backup Battery 5 minute RTC after main battery removal, 168 hours RTC in main battery low power
- Charging method: Enclosed power supply, separate USB cable, separate Car charging adapter, separate cradle CRD19 series with spare battery bay
- Battery charging time: Ca. 4 or 8 hours when charging through Power supply, Ca. 6 or 12 hours when charging by USB cable connected to PC (resp. standard or High-capacity battery)

2D Imager Optics

- Light source: Illumination 4 red LEDs 630 nm, aiming 2 green LEDs
- Scan method: CMOS area sensor
- Scan rate: Up to 30 fps
- Reading pitch angle: -50 to 0°, 0 to +50°
- Reading skew angle: -60 to 0°, 0 to +60°
- Reading tilt angle: 360°
- Curvature: R>15 (EAN8), R>20 (EAN13)
- Min. Resolution at PCS 0.9: 0.127 mm / 5 mil at PDF 417, 0.1mm / 3.9 mil at Code 39, 0.169 mm, 6.7 mil at Data Matrix, QR Code
- Min. PCS value: 0.45
- Field of view: Horizontal 47°, Vertical 37.5°
- Depth of field: At PCS 0.9 PDF417 50 - 215 mm / 1.97 - 8.46 in (0.339 mm / 13 mil), 95 - 135 mm / 3.74 - 5.31 in (0.127 mm / 5 mil)

Supported Symbologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Aztec Code, Aztec Runes, Composite codes, Codablock F, Data Matrix, (ECC200/ECO-140), Maxi Code (mode 2~5), MicroPDF417, Micro QR Code, PDF417, QR code

Durability

- Temperature in operation: -10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 20 - 80 % (non-condensing)
- Humidity in storage: 20 - 90 % (non-condensing)
- Drop test: 1.2 m / 4 ft drop onto concrete surface
- Protection rate: IP 54

Physical

- Dimensions (w x h x d): 62.3 x 140.8 x 25.5 mm / 2.45 x 5.54 x 1.00 in
- Weight body: Ca. 200g / 7.1 oz (incl. battery)
- Case: Black

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

Enclosed items

- Power supply 230V-5V/500mA
- Standard Lithium-Ion Polymer battery 4.2 V 1440 mAh
- USB cable (client to host)
- Leather Case
- Belt clip
- Neck strap
- Handstrap
- Ear microphone
- Getting Started disc
- Stylus

Sold separately

- CRD 19 single cradle for charging & USB communication
- CRD 19 E4 multi-cradle for charging & Ethernet communication
- High-capacity Lithium-Ion Polymer battery 4.2 V 2600 mAh
- Car charging adapter
- Car holder kit

Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg, NY - Seattle, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang

Opticon Sensors Europe B.V.
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM