

OPI4002

2D CMOS imager

IEEE 802.15.4

Wireless Dongle

+ Related products

PX25

- Data Collector
- 2D CMOS imager
- IrDA, Bluetooth
- Equipped with powerjack

OPI2201

- Cabled device
- 2D CMOS imager with auto-focus
- RS232, Keyboard Wedge, USB

OPI2002

- Cabled device
- 2D CMOS imager
- RS232, Keyboard Wedge, USB



Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

Operating keys

- Entry options:
1 scan key

Communication

- IEEE 802.15.4: range up to 30 m, 1 to 1 connection (OPI4002 scanner to USB(HID) dongle)

Power

- Rechargeable battery: Lithium-Ion 3.6 V 1150 mAh
- Operating time: Ca. 30 hours (1 scan / 5 sec)
- Charging method: Separate cradle CHG4001, separate power supply
- Battery charging time: Ca. 3 hours (full charge)

Barcode scanner Optics

- Light source: Illumination 4 red LEDs 630 nm, aiming 2 green LEDs 527 nm
- Scan method: CMOS area sensor, SXGA (1.3 million pixels), gray scale
- Scan rate: Up to 30 fps
- Reading pitch angle: -50 to 0°, 0 to +50°
- Reading skew angle: -60 to 0°, 0 to +60°
- Reading tilt angle: 360°

2D Imager Optics

- Focal plane: 85 mm / 3.35 in from window
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.1 mm / 4 mil for Code 39, 0.127 mm / 15 mil for PDF417
- Min. PCS value: 0.45
- Field of view: Horizontal 47°, Vertical 37.5°
- Depth of field: at *PDF417* and Code 39
25 - 130 mm / 0.98 - 5.12 in (res 0.399 mm / 13 mil),
48 - 80 mm / 1.89 - 3.15 in (res 0.127 / 5 mil),
30 - 105 mm / 1.18 - 4.13 in (0.25 / 10 mil),
55 - 75 mm / 2.17 - 2.95 in (0.1 / 4 mil)

Supported Symbologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Aztec Code, Aztec Runes, Composite codes, Data Matrix (ECC200/ECO-140), Maxi Code (mode 2-5), MicroPDF417, Micro QR Code, PDF417, QR code

Durability

- Temperature in operation: -0 to 40 °C / -32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 5 - 90 % (non-condensing)
- Humidity in storage: 5 - 90 % (non-condensing)
- Ambient light immunity: Fluorescent 10,000 lx max, Direct sun 100,000 lx max, Incandescent 10,000 lx max
- Antistatic electricity: 15 kV (non destructive)
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 10 - 100 Hz with 2G for 1 hour
- Protection rate: IP 42

Physical

- Dimensions (w x h x d):
59 x 164 x 43 mm / 2.32 x 6.46 x 1.69 in
- Weight body: Ca. 125 g / 4.4 oz (excl. battery)
- Case: ABS, White

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

Sold separately

- CHG4001 charging cradle
- OPA1001 IEE 802.15.4 dongle (with USB connector integrated)

Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg, NY - Seattle, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang

Opticon Sensors Europe B.V.
European headquarters
Opaalaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM